

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number
WO 2005/054033 A1

- (51) International Patent Classification⁷: **B62D 3/12**, (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (21) International Application Number: PCT/AU2004/001681
- (22) International Filing Date: 2 December 2004 (02.12.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 2003906676 2 December 2003 (02.12.2003) AU
- (71) Applicant (for all designated States except US): **BISHOP INNOVATION LIMITED** [AU/AU]; 10 Waterloo Road, North Ryde, NSW 2113 (AU).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **BAXTER, John** [AU/AU]; 42 Hawthorne Avenue, Chatswood, NSW 2067 (AU).
- (74) Agent: **PAPPAS, Frank**; Bishop Innovation Limited, P.O. Box 135, North Ryde, NSW 1670 (AU).
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: STEERING SYSTEM



(57) Abstract: A rack and pinion steering gear for a vehicle comprising a housing (2), a pinion (1) rotatable about a first axis (14) in the housing, a rack (7) laterally displaceable with respect to the housing, and an intermediate gear (8) interposed between, and meshing with, the pinion (1) and with the rack (7), the intermediate gear (8) rotatable about a second axis (9). The second axis (9) is laterally movable with respect to the housing as a function of at least one vehicle parameter, by an actuator mechanism, thereby varying the relationship between the angular displacement of the pinion and the lateral displacement of the rack as a function of the vehicle parameter.